NSN 5305-01-337-5990

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-5990 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.694 inches **Fastener Length:** Between 2.179 inches and 2.209 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.829 inches and 0.892 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.490 inches and 1.510 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Special Features:** Red dye or paint on thread end before lubrication Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Bac 5861, cage81205 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5305-01-337-5990

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0