

View Online at <https://aerobasegroup.com/nsn/5305-01-337-6000>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.469 inches

**Fastener Length:**

Between 1.454 inches and 1.484 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.578 inches and 0.634 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.990 inches and 1.010 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Nas 4006 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1790 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0