## NSN 5305-01-337-6003

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-6003

Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
0.363 inches					
Fastener Length:					
Between 0.785 inches and 0.832 inches					
Head Style:					
Flat countersunk undercut					
Head Diameter:					
Between 0.350 inches and 0.381 inches					
Head Height:					
Between 0.044 inches and 0.046 inches					
Grip Diameter:					
Between 0.1890 inches and 0.1895 inches					
Internal Drive Style:					
High-torque					
Thread Diameter:					
0.190 inches					
Grip Length:					
Between 0.428 inches and 0.448 inches					
Features Provided:					
O ring					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
160000 pounds per square inch					
Countersink Angle:					
Between 99.0 degrees and 101.0 degrees					
Surface Finish:					
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads					
Product Name:					
Navy special project					
Material:					
Rubber butadiene-acrylonitrile class nbr ringtitanium alloy uns r56400 fastener					
Material Specification:					
Ams 4967 assn standard single material response fastener					
Surface Treatment:					
Phosphate fastener					

**Surface Treatment Specification:** 

Bac5861, cagec 81205 mfr ref single treatment response fastener

## NSN 5305-01-337-6003

Close Tolerance Screw - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0