## NSN 5305-01-337-6008

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-6008

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.345 inches   |
| Fastener Length:   |
| Between 0.768 inches and 0.798 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.345 inches and 0.383 inches  |
| Grip Diameter:   |
| Between 0.1890 inches and 0.1895 inches  |
| Internal Drive Style:  |
| High-torque  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.428 inches and 0.448 inches  |
| Features Provided:   |
| Cetyl alcohol lubricant  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Surface Finish:  |
| 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads              |
| Product Name:  |
| Navy special project   |
| Special Features:  |
| Red dye or paint on thread end before lubrication  |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment:   |
| Phosphate  |
| Surface Treatment Specification:   |
| Bac 5861, cage81205 mfr ref single treatment response  |
| Thread Series Designator:  |
|  |

Unjf

## NSN 5305-01-337-6008

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

