## NSN 5305-01-337-6011

Close Tolerance Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-337-6011

3a         Thread Direction:         Right-hand         Thread Length:         0.363 inches         Fastener Length:         Between 0.722 inches and 0.769 inches         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Height:         Between 0.44 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Hernal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Lameter:         0.190 inches         Outprist         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thread Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         3.2.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	Thread Class:
Thread Direction:         Right-hand         Thread Length:         0.363 inches         Fastener Length:         Between 0.722 inches and 0.769 inches         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.44 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         Oring         Thread Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         10 ring         Thread Strength (psi):         160000 pounds per square inch         Countersink Angle:         82.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	
Right-hand         Right-hand         Thread Length:         0.363 inches         Fastener Length:         Between 0.722 inches and 0.769 inches         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.1490 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         Oring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	
Tread Length:         0.363 inches         Fastener Length:         Between 0.722 inches and 0.769 inches         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.1490 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         Oring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadas         Product Name:         Navy special project	
0.363 inchesFastener Length:Between 0.722 inches and 0.769 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.350 inches and 0.381 inchesHead Height:Between 0.344 inches and 0.046 inchesGrip Diameter:Between 0.1890 inches and 0.1895 inchesInternal Drive Style:High-torqueThread Diameter:0.190 inches0.190 inchesGrip Diameter:0.190 inches191 Thread Diameter:0.190 inches192 Thread Diameter:0.190 inches193 Thread Pierter:0.190 inches194 Diameter:0.190 inches195 Diameter:0.190 inches196 Diameter:0.190 inches197 Diameter:0.190 inches198 Diameter:0.190 inches199 Diameter:0.190 inches190 Inches190 Diameter:191 Diameter:192 Diameter:193 Diameter:193 Diameter:194 Diameter:195 Diameter:195 Diameter:196 Diameter:197 Diameter:198 Diameter:198 Diameter:198 Diameter:199 Diameter:	5
Fasterer Length:         Between 0.722 inches and 0.769 inches         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	-
Between 0.72         Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Cty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 9.0. degrees and 101.0 degrees         Sur incircinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	
Head Style:         Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thread Style Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	-
Flat countersunk undercut         Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Fread Value         Oring         Thready Oty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	
Head Diameter:         Between 0.350 inches and 0.381 inches         Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project	-
Between 0.350 inches and 0.381 inches Head Height: Between 0.044 inches and 0.046 inches Grip Diameter: Between 0.1890 inches and 0.1895 inches Internal Drive Style: High-torque Thread Diameter: 0.190 inches Grip Length: Between 0.365 inches and 0.385 inches Features Provided: O ring Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Froduct Name: Navy special project Material:	
Head Height:         Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Product Name:         Navy special project         Material:	
Between 0.044 inches and 0.046 inches         Grip Diameter:         Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Furduet Name:         Navy special project         Material:	
Grip Diameter:Between 0.1890 inches and 0.1895 inchesInternal Drive Style:High-torqueThread Diameter:0.190 inchesGrip Length:Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	-
Between 0.1890 inches and 0.1895 inches         Internal Drive Style:         High-torque         Thread Diameter:         0.190 inches         Grip Length:         Between 0.365 inches and 0.385 inches         Features Provided:         O ring         Thready Qty Per Inch (tpi):         32         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Pounce Inch (tpi):         Auge Inch (tpi):         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads         Pounce Name:         Navy special project	
High-torqueThread Diameter:0.190 inchesGrip Length:Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	-
High-torqueThread Diameter:0.190 inchesGrip Length:Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	Internal Drive Style:
Thread Diameter:0.190 inchesGrip Length:Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	-
Grip Length:Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	
Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	0.190 inches
Between 0.365 inches and 0.385 inchesFeatures Provided:O ringThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	Grip Length:
O ring Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threadsProduct Name:Navy special projectMaterial:	Features Provided:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	O ring
<ul> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Countersink Angle:</li> <li>Between 99.0 degrees and 101.0 degrees</li> <li>Surface Finish:</li> <li>32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads</li> <li>Product Name:</li> <li>Navy special project</li> <li>Material:</li> </ul>	Thready Qty Per Inch (tpi):
160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	32
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	Min. Tensile Strength (psi):
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	160000 pounds per square inch
Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Material:	Countersink Angle:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads <b>Product Name:</b> Navy special project <b>Material:</b>	Between 99.0 degrees and 101.0 degrees
Product Name: Navy special project Material:	Surface Finish:
Navy special project Material:	32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:	Product Name:
	Navy special project
Rubber butadiene-acrylonitrile class nbr ringtitanium alloy uns r56400 fastener	Material:
	Rubber butadiene-acrylonitrile class nbr ringtitanium alloy uns r56400 fastener
Material Specification:	Material Specification:
Ams 4967 assn standard single material response fastener	Ams 4967 assn standard single material response fastener
Surface Treatment:	Surface Treatment:
Phosphate fastener	Phosphate fastener
Surface Treatment Specification:	Surface Treatment Specification:
	Bac5861, cagec 81205 mfr ref single treatment response fastener
	Bac5861, cagec 81205 mfr ref single treatment response fastener

## NSN 5305-01-337-6011

Close Tolerance Screw - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

