## NSN 5305-01-337-6017

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-6017

Thread Class:
3a

Thread Direction:
Right-hand
Thread Length:

Fastener Length:

Between 1.079 inches and 1.109 inches

**Head Style:** 

0.469 inches

Flat countersunk

**Head Diameter:** 

Between 0.456 inches and 0.508 inches

**Grip Diameter:** 

Between 0.2490 inches and 0.2495 inches

**Internal Drive Style:** 

High-torque

**Thread Diameter:** 

0.250 inches

**Grip Length:** 

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

28

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Surface Finish:** 

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Product Name:** 

Navy special project

Special Features:

Tapped hole in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.380 nom. Inch. Injection port 0.120 nom. In. Lg; 0.060 nom. In. Wide

Material:

Titanium alloy uns r56400

**Material Specification:** 

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:** 

Phosphate

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5305-01-337-6017

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0