

View Online at <https://aerobasegroup.com/nsn/5305-01-337-6984>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.906 inches

**Fastener Length:**

Between 2.141 inches and 2.171 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.047 inches and 1.144 inches

**Grip Diameter:**

Between 0.5610 inches and 0.5615 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.240 inches and 1.260 inches

**Thready Qty Per Inch (tpi):**

18

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Special Features:**

Tapped hole in head 0.138-32 unjc-3b threads. Distance from top of head to injection port 0.910 nom. Inch. Injection port 0.120 nom. In. Lg; 0.060 nom. In. Wide

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0