NSN 5305-01-337-6993

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-6993

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.338 inches
Fastener Length:
Between 0.823 inches and 0.853 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Material: Titanium alloy uns r56400
Titanium alloy uns r56400
Titanium alloy uns r56400 Material Specification:
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment:
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification:
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas 4006 assn standard single treatment response Thread Series Designator: Unjf
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas 4006 assn standard single treatment response Thread Series Designator: Unjf Specification Data:
Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas 4006 assn standard single treatment response Thread Series Designator: Unjf

N/a

NSN 5305-01-337-6993

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0