## NSN 5305-01-337-6995

**Thread Class:** 

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-6995

3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 1.073 inches and 1.103 inches
Head Style:
Fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1123 professional/industrial association standard
Shelf Life:
N/a

## NSN 5305-01-337-6995

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0