NSN 5305-01-337-9127

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-337-9127

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.370 inches |
| Fastener Length: |
| Between 0.917 inches and 0.947 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.473 inches and 0.492 inches |
| Head Height: |
| Between 0.162 inches and 0.175 inches |
| Grip Diameter: |
| - Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.552 inches and 0.572 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Navy special project |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas7904 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-337-9127

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

