

View Online at <https://aerobasegroup.com/nsn/5305-01-338-0383>

Fastener Length:

Between 1.495 inches and 1.500 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.292 inches and 0.332 inches

Internal Drive Style:

Slot

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Nonmachine Thread Diameter:

0.164 inches

Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1109 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1116 or steel comp 1117 or steel comp 1118

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 3 federal specification 1st treatment response or mil-c-81562 type 2, cl 3 military specification 1st treatment response or astm b633 type 2, cl fe/zn 5 assn standard 2nd treatment response

Specification Or Standard:

1 type and 2s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.