NSN 5305-01-338-0559

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-0559

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.232 inches
Fastener Length:
Between 0.717 inches and 0.757 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.194 inches and 0.225 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Titanium alloy uns r56400
Screw Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1221 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-338-0559

Machine Screw - Page 2 of 2

Fiig: A500d0

