NSN 5305-01-338-0917

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-0917 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.431 inches and 0.481 inches **Fastener Length:** Between 0.753 inches and 0.783 inches **Head Style:** Flat countersunk **Head Diameter:** 0.081 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Product Name:** Navy special project Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjc **Specification Data:** 80205-nas8806 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-338-0917

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0