NSN 5305-01-338-0919

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-0919 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.511 inches and 0.541 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.246 inches and 0.280 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7401 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-338-0919

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0