NSN 5305-01-338-0923

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-0923

80205-nas1790 professional/industrial association standard

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.338 inches
Fastener Length:
Between 0.650 inches and 0.665 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Titanium alloy uns r56400
·
Material Specification:
Material Specification:
Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment:
Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum
Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification:
Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response Surface Treatment: Aluminum Surface Treatment Specification: Nas 4006 assn standard single treatment response

NSN 5305-01-338-0923

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0