NSN 5305-01-338-1314

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-338-1314

| Thread Class | |
|----------------|---|
| 3a | |
| Thread Direct | tion: |
| Right-hand | |
| Thread Lengt | ih: |
| 0.656 inches | |
| Fastener Len | gth: |
| Between 0.734 | 4 inches and 0.781 inches |
| Head Style: | |
| Hexagon | |
| Head Height: | |
| Between 0.10 | 5 inches and 0.120 inches |
| Width Betwee | en Flats: |
| Between 0.30 | 5 inches and 0.314 inches |
| Internal Drive | e Style: |
| Cross recess t | type 1 |
| Thread Diame | eter: |
| 0.190 inches | |
| Thready Qty | Per Inch (tpi): |
| 32 | |
| Screw Materia | al: |
| Titanium alloy | uns r56400 |
| Screw Materia | al Specification: |
| Ams4928 assr | n standard single material response or ams4967 assn standard single material response |
| Screw Surfac | e Treatment: |
| Aluminum | |
| Thread Series | s Designator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Meas | ure: |
| | |
| Demilitarizati | on: |
| No | |
| Fiig: | |
| A500d0 | |