NSN 5305-01-338-2833

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-2833 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 1.075 inches and 1.122 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.475 inches and 0.507 inches **Head Height:** Between 0.071 inches and 0.073 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.678 inches and 0.698 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Rubber butadiene-acrylonitrile class nbr ringnickel alloy 718 fastener **Material Specification:** Ams 5662 assn standard single material response fastener **Surface Treatment:** Passivate fastener **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-338-2833

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0