NSN 5305-01-338-3140

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3140

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.354 inches and 0.425 inches
Fastener Length:
Between 0.910 inches and 0.935 inches
Head Style:
Flat countersunk
Head Diameter:
0.111 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:
Unjf
Specification Data:
80205-nas1790 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
NI-

No

NSN 5305-01-338-3140

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0