NSN 5305-01-338-3144

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3144

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.345 inches |
| Fastener Length: |
| Between 1.080 inches and 1.110 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| |
| Between 0.122 inches and 0.133 inches |
| Grip Diameter: Between 0.1890 inches and 0.1895 inches |
| |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.740 inches and 0.760 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Product Name: |
| Navy special project |
| Special Features: |
| Surface treatment contains fluoride |
| Color: |
| Red threads |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification: |
| Bac 5861, cagec 81205 mfr ref single treatment response |
| Thread Series Designator: |
| Unf |
| |

NSN 5305-01-338-3144

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

