NSN 5305-01-338-3150

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3150 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.189 inches and 0.199 inches **Fastener Length:** Between 1.030 inches and 1.060 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.346 inches and 0.376 inches **Head Height:** Between 0.115 inches and 0.135 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.313 inches and 0.375 inches **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Sleeve fits on shank portion of screw up to bearing surface of head and is also spring loaded Material: Iron alloy 660 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, ty1, 2 or 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-338-3150

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0