NSN 5305-01-338-3150

Panel Screw Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-338-3150



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.189 inches and 0.199 inches

Fastener Length:

Between 1.030 inches and 1.060 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.346 inches and 0.376 inches

Head Height:

Between 0.115 inches and 0.135 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.313 inches and 0.375 inches

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.1406 inches and 0.1426 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Special Features:

Sleeve fits on shank portion of screw up to bearing surface of head and is also spring loaded

Material:

Iron alloy 660

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, ty1, 2 or 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-01-338-3150

Panel Screw Assembly - Page 2 of 2

Fiig: A003b0

