## NSN 5305-01-338-3260

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3260 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.232 inches **Fastener Length:** Between 1.092 inches and 1.122 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.194 inches and 0.225 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Titanium alloy uns r56400 **Screw Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1221 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-338-3260

Machine Screw - Page 2 of 2



Fiig:

A500d0