NSN 5305-01-338-3352

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3352

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.469 inches |
| Fastener Length: |
| Between 1.829 inches and 1.859 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.586 inches and 0.637 inches |
| Grip Diameter: |
| Between 0.3427 inches and 0.3432 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Features Provided: |
| Cetyl alcohol lubricant |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Special Features: |
| Red dye or paint on thread end before lubrication |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification: |
| Bac 5861, cage81205 mfr ref single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |

NSN 5305-01-338-3352

Close Tolerance Screw - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0