NSN 5305-01-338-3359

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3359

Thread Olever
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.276 inches and 0.338 inches
Fastener Length:
Between 0.761 inches and 0.791 inches
Head Style:
Flat countersunk
Head Diameter:
0.083 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:
Unjf
Specification Data:
80205-nas1790 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-338-3359

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0