NSN 5305-01-338-3363

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-3363

view Offiline at https://defobasegroup.com/nsi//0000-01-000-0000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.338 inches
Fastener Length:
Between 0.511 inches and 0.541 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Features Provided:
Dry film lubricant
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5735 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5305-01-338-3363

Close Tolerance Screw - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

80205-nas1790 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0