## NSN 5305-01-338-4049

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-4049
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 1.079 inches and 1.109 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.456 inches and 0.508 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Special Features:
$Tapped \ hole \ in \ head \ 0.138-32 \ unjc-3b \ threads. \ Distance \ from \ top \ of \ head \ to \ injection \ port \ 0.230 \ nom. \ Inch. \ Injection \ port \ 0.120 \ nom. \ In. \ Lg;$
0.060 nom. In. Wide
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

## NSN 5305-01-338-4049

Close Tolerance Screw - Page 2 of 2



	• •					
ın	18	<i>(</i> )+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A003b0