## NSN 5305-01-338-4060

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-4060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.496 inches and 0.526 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.226 inches and 0.257 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Product Name:** Navy special project Material: Titanium alloy uns r56400 **Material Specification:** 

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:** 

Aluminum

**Thread Series Designator:** 

Unjc

**Specification Data:** 

80205-nas8802 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-338-4060

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0