NSN 5305-01-338-4062

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-4062 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 1.387 inches and 1.434 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.475 inches and 0.506 inches **Head Height:** Between 0.071 inches and 0.073 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.990 inches and 1.010 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Product Name:** Navy special project Material: Rubber butadiene-acrylonitrile class nbr ringtitanium alloy uns r56400 fastener **Material Specification:**

Surface Treatment:

Phosphate fastener

Surface Treatment Specification:

Bac5861, cagec 81205 mfr ref single treatment response fastener

Ams 4967 assn standard single material response fastener

NSN 5305-01-338-4062

Close Tolerance Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A003b0