

View Online at <https://aerobasegroup.com/nsn/5305-01-338-4975>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.531 inches

**Fastener Length:**

Between 2.827 inches and 2.859 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.623 inches and 0.633 inches

**Head Height:**

0.133 inches

**Grip Diameter:**

Between 0.3112 inches and 0.3117 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.3125 inches

**Grip Length:**

2.312 inches

**Width Across Flats:**

Between 0.1885 inches and 0.1905 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas335-26 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.