## NSN 5305-01-338-7089

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-338-7089



## **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 2.188 inches and 2.250 inches

## Fastener Length:

Between 2.156 inches and 2.250 inches

#### **Head Style:**

Flat countersunk

### Head Diameter:

0.160 inches

## Internal Drive Style:

Torque set

## **Thread Diameter:**

0.375 inches

## Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

## Countersink Angle:

Between 99.0 degrees and 101.0 degrees

## Screw Material:

Iron alloy 660

## **Screw Material Specification:**

Ams 5737 assn standard single material response

## **Screw Surface Treatment:**

Passivate

## Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

## **Thread Surface Finish:**

32.0 microinches

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas1102 professional/industrial association standard

## Shelf Life:

N/a

# NSN 5305-01-338-7089

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

