NSN 5305-01-338-7293

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-7293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.133 inches and 0.188 inches **Fastener Length:** Between 0.158 inches and 0.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.091 inches and 0.096 inches **Head Height:** Between 0.057 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.060 inches Width Across Flats: Between 0.500 inches and 0.510 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-338-7293

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0