

View Online at <https://aerobasegroup.com/nsn/5305-01-338-7304>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

Between 0.890 inches and 0.937 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.477 inches and 0.508 inches

Head Height:

Between 0.582 inches and 0.602 inches

Shoulder Diameter:

0.2807 inches first shoulder and 0.2997 inches first shoulder

Shoulder Length:

0.3788 inches first shoulder

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Features Provided:

O ring and cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-s-83488, ty2, cl3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-83488 spec.