## NSN 5305-01-338-7306

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-7306 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.130 inches and 0.197 inches **Fastener Length:** Between 0.390 inches and 0.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3765 inches and 0.3813 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches **Features Provided:** Cetyl alcohol lubricant and o ring Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Stainless steel **Material Specification:** 23-112, ty c cagec 76301 mfr ref single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5305-01-338-7306

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0