
# NSN 5305-01-338-7584

Machine Screw - Page 1 of 2





Thread Class:

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 2.608 inches and 2.685 inches

#### Fastener Length:

Between 2.672 inches and 2.717 inches

#### Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

#### Width Between Flats:

Between 0.305 inches and 0.314 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

# Screw Material:

Iron alloy 660

#### **Screw Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### **Screw Surface Treatment:**

Passivate

#### Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Bearing Surface Of Head Surface Finish:

63.0 microinches

## Thread Surface Finish:

32.0 microinches

# **Thread Series Designator:**

Unjf

# Specification Data:

80205-nas1802 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5305-01-338-7584

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

