NSN 5305-01-338-8162

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-8162 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.693 inches and 0.703 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.286 inches and 0.303 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response or ams4928 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8803 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-338-8162

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0