NSN 5305-01-338-9348

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-338-9348

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.425 inches
Fastener Length:
Between 1.473 inches and 1.503 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.465 inches and 0.510 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Grip Length:
Between 1.053 inches and 1.073 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees Surface Finish:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color: Red threads
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color: Red threads Material:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color: Red threads Material: Titanium alloy uns r56400
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color: Red threads Material: Titanium alloy uns r56400 Material Specification:
Between 99.0 degrees and 101.0 degrees Surface Finish: 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Product Name: Navy special project Special Features: Surface treatment contains fluoride Color: Red threads Material: Titanium alloy uns r56400 Material Specification: Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Bac 5861, cagec 81205 mfr ref single treatment response

NSN 5305-01-338-9348

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A003b0