

View Online at <https://aerobasegroup.com/nsn/5305-01-339-0909>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.203 inches

Fastener Length:

0.410 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.031 inches and 0.068 inches

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Material:

Steel comp 301 primary washer or steel comp 302 primary washer or steel comp 302b primary washer or steel comp 303 primary washer or steel comp 303se primary washer or steel comp 304 primary washer or steel comp 304l primary washer or steel comp 305 primary washer or steel comp 308 primary washer or steel comp 309 primary washer or steel comp 309s primary washer or steel comp 310 primary washer or steel comp 310s primary washer or steel comp 314 primary washer or steel comp 316 primary washer or steel comp 316l primary washer or steel comp 317 primary washer or steel comp 321 primary washer or steel comp 347 primary washer or steel comp 348 primary washer or steel comp 384 primary washer or steel comp 385 primary washercopper alloy stand-offsteel fastener

Surface Treatment:

Passivate primary washercadmium stand-offcadmium fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response stand-offqq-p-416 type 1 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0