NSN 5305-01-339-1408

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-1408

Paread Class: 3a Firead Direction: Righ-hand Thread Length: Between 0.620 inches and 0.750 inches Fastener Length: Between 0.220 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Peight: Between 0.365 inches and 0.375 inches Head Peight: Between 0.365 inches and 0.375 inches Head Style: Between 0.326 inches and 0.326 inches Head Style: Between 0.326 inches and 0.325 inches Head Style: Between 0.326 inches and 0.326 inches Head Style: Between 0.326 inches and 0.390 inches Head Style: Between 0.327 inches and 0.390 inches Between 0.387 inches and 0.390 inches Betw
Thread Direction: Right-hand Thread Length: Between 0.620 inches and 0.750 inches Fastener Length: Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Uith Across Flats: Between 0.187 inches and 0.190 inches Thready Qity Per Inch (tpi): 20 Mint-Tossile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Right-hand Thread Length: Between 0.620 inches and 0.750 inches Fastenr Length: Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.365 inches and 0.375 inches Head Height: Between 0.424 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Mith Across Flats: Between 0.187 inches and 0.190 inches Thread Diameter: 0.250 inches Mith Across Flats: Between 0.187 inches and 0.190 inches Thread Qup Per Inch (tpi): 120 Min Tensile Strength (psi): 160000 pounds per square inch Material Plastic polyramide locking featureiron alloy 660 fastener Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Thread Length: Between 0.620 inches and 0.750 inches Fastener Length: Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.365 inches and 0.375 inches Head Height: Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Outsous Width Across Flats: Between 0.187 inches and 0.190 inches Thread Quy Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification:
Advent 0.420 inches and 0.750 inches Fastener Length: Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches With Across Flats: Between 0.187 inches and 0.190 inches Thready Oty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Metrial: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Atorsal Stangt and single material response fastener or ams 5737 assn standard single material response fastener
Fastener Length: Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Head Height: Between 0.244 inches and 0.250 inches Head Height: Between 0.244 inches and 0.250 inches Head Netween 0.244 inches and 0.250 inches Forking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches With Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min Tensile Strength (psi): 10000 pounds per square inch Metrial: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Atterial Specification:
Between 0.720 inches and 0.750 inches Head Style: Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches With Across Flats: Between 0.187 inches and 0.190 inches Thready Oty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Anser 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn standard single material response fastener or ams 5737 assn
Head Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesLocking Feature:Patch threads or pellet threads or strip threadsInternal Drive Style:Patch threads or pellet threads or strip threadsInternal Drive Style:Otz Diameter:0.250 inchesBetween 0.187 inches and 0.190 inchesPatch Across Flats:Patevang 0.187 inches and 0.190 inchesDiameter 0.187 inches 0.190 inchesDiameter 0.190 inchesDiameter 0.190 inchesDiameter 0.190 inchesDiameter 0.190 inchesDiameter 0.190 inchesDia
Flat chamfer Head Diameter: Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches With Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 10000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Anse 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Head Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesLocking Feature:Patch threads or pellet threads or strip threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Oty Per Inch (tpi):20Min Tensile Strength (psi):10000 pounds per square inchMaterial:Pastic polyamide locking featureiron alloy 660 fastenerAins 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Between 0.365 inches and 0.375 inches Head Height: Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ans 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Head Height:Between 0.244 inches and 0.250 inchesBetween 0.244 inches and 0.250 inchesLocking Feature:Patch threads or pellet threads or strip threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):10000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMetrial Specification:Ans 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Between 0.244 inches and 0.250 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Arso 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Locking Feature:Patch threads or pellet threads or strip threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWith Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Patch threads or pellet threads or strip threadsInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Internal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Thread Diameter:0.250 inchesWidth Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 16000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification:
Width Across Flats:Between 0.187 inches and 0.190 inchesThready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Thready Qty Per Inch (tpi):20Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification:
Min. Tensile Strength (psi):160000 pounds per square inchMaterial:Plastic polyamide locking featureiron alloy 660 fastenerMaterial Specification:Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Material: Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Plastic polyamide locking featureiron alloy 660 fastener Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-339-1408

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

