

View Online at <https://aerobasegroup.com/nsn/5305-01-339-2060>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.298 inches and 0.348 inches

**Fastener Length:**

Between 0.496 inches and 0.526 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.338 inches and 0.381 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Plastic polyamide locking feature iron alloy 660 fastener

**Material Specification:**

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas7503 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0