NSN 5305-01-339-3181

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-3181 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.290 inches **Fastener Length:** Between 0.765 inches and 0.795 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.133 inches and 0.138 inches **Second Diameter From Head:** Between 0.095 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.020 inches and 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.420 inches and 0.440 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 630 **Material Specification:** Ams5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unc

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-339-3181

Externally Relieved Body Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0