## NSN 5305-01-339-3941

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-3941

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.445 inches
Fastener Length:
Between 0.873 inches and 0.893 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.335 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Width Across Flats:
Between 0.125 inches and 0.127 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Special Features:
Furnished with keyway
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-339-3941

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0