# NSN 5305-01-339-3946

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-339-3946

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

0.622 inches

#### Fastener Length:

Between 0.652 inches and 0.682 inches

Head Style:

Knurled no. 2

Head Diameter:

0.451 inches

Head Height:

0.290 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.020 inches and 0.031 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

#### Material:

Aluminum alloy 6061 headsteel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener

## **Material Specification:**

Qq-a-225/8 federal specification single material response headmil-s-5059 military specification single material response primary washerastm a580 assn standard single material response springqq-a-225/8 federal specification single material response stand-offastm a493 assn standard all material responses fastener

## Surface Treatment:

Anodize headpassivate primary washerpassivate springanodize stand-offpassivate fastener

## Surface Treatment Specification:

Mil-a-8625 type 1, cl 1 military specification single treatment response headqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625 type 1, cl 1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

#### Thread Series Designator:

Unf

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig: