NSN 5305-01-339-5007

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-5007 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.168 inches **Fastener Length:** Between 1.200 inches and 1.260 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.937 inches **Head Height:** Between 0.816 inches and 0.825 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c **Hole Configuration Style:** Round internal hexagon Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1, cl 2 federal specification single treatment response

Unrc

Thread Series Designator:

NSN 5305-01-339-5007

Socket Head Cap Screw - Page 2 of 2



S	pec	ific	cati	on	Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0