## NSN 5305-01-339-5013

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-5013 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.223 inches and 1.253 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.465 inches and 0.510 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.803 inches and 0.823 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads **Product Name:** Navy special project **Special Features:** Surface treatment contains fluoride Color: Red threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Phosphate

**Surface Treatment:** 

**Surface Treatment Specification:** 

Bac 5861, cagec 81205 mfr ref single treatment response

## NSN 5305-01-339-5013

Close Tolerance Screw - Page 2 of 2



Thread Series Designator	r:
--------------------------	----

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0