NSN 5305-01-339-5210

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-5210 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.207 inches and 0.274 inches **Fastener Length:** Between 1.968 inches and 1.998 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Navy special project **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1218 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-339-5210

Machine Screw - Page 2 of 2



Fiig:

A500d0