NSN 5305-01-339-8164

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-339-8164 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.511 inches and 0.541 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.280 inches and 0.337 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1152 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-339-8164

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0