NSN 5305-01-339-8630



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-339-8630 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.190 inches **Fastener Length:** Between 0.422 inches and 0.452 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjf

Specification Data:

80205-nas1216 professional/industrial association standard

NSN 5305-01-339-8630

Machine Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0