NSN 5305-01-340-3998

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-340-3998 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.215 inches **Fastener Length:** 0.605 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.229 inches and 0.239 inches **Head Height:** Between 0.050 inches and 0.060 inches **First Diameter From Head:** 0.187 inches **Second Diameter From Head:** 0.140 inches **Third Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.125 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.325 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.390 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-340-3998

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0