

View Online at <https://aerobasegroup.com/nsn/5305-01-340-4000>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.435 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

Between 0.084 inches and 0.089 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.310 inches and 0.320 inches

**Point Style:**

Pointless

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Black

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl 4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.