

View Online at <https://aerobasegroup.com/nsn/5305-01-340-5065>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.245 inches and 0.255 inches

Fastener Length:

Between 0.594 inches and 0.624 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.145 inches and 0.155 inches

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Material:

Steel comp 302 springsteel comp 301 stand-off or steel comp 302 stand-off or steel comp 302b stand-off or steel comp 303 stand-off or steel comp 303se stand-off or steel comp 304 stand-off or steel comp 304l stand-off or steel comp 305 stand-off or steel comp 308 stand-off or steel comp 309 stand-off or steel comp 309s stand-off or steel comp 310 stand-off or steel comp 310s stand-off or steel comp 314 stand-off or steel comp 316 stand-off or steel comp 316l stand-off or steel comp 317 stand-off or steel comp 321 stand-off or steel comp 347 stand-off or steel comp 348 stand-off or steel comp 384 stand-off or steel comp 385 stand-offiron alloy 660 fastener

Material Specification:

Ams 5732 assn standard single material response fastener

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: